

# BE400-UK

400-1500VA

Peace of mind from the world's most trusted UPS.

## PRODUCT FEATURES

- Back up and protect your hardware and data during power outages, surges and spikes.
- Protect secondary electronics from surges and spikes without reducing battery power used to run primary electronics during an outage.
- Periodic battery self-test ensures early detection of a battery that needs to be replaced.
- Provides early-warning fault analysis on batteries enabling timely preventive maintenance
- Maximizes battery performance, life, and reliability through intelligent, precision charging.
- Easy recovery from overloads; no need to replace a fuse.
- Provides notification of changing utility power and UPS power conditions
- Quickly understand unit and power status with visual indicators.
- Ensures the product has been tested and approved to work safely with the connected service provider
- equipment and within the specified environment.
- Reserves power capacity and run time for connected equipment that require UPS battery back-up while providing surge only protection for less critical equipment
- Provides protection of connected equipment from power surges on the data lines.
- Provides peace of mind by providing professional data recovery services in the event data is lost due to the failure of the unit.
- Easy recovery from overloads; no need to replace a fuse.

# Technical Specifications

BE400-UK	
Output	
Output Power Capacity	240 Watts / 400 VA
Max Configurable Power	240 Watts / 400 VA
Nominal Output Voltage	230V VA
Topology	Standby
Waveform Type	Stepped approximation to a sinewave
Output Connections	(4)BS 1363(Battery Backup) (4)BS 1363(Surge Protection)
Input	
Nominal Input Voltage	230V
Input Frequency	50/60 Hz
Input Connections	British BS1363A(Surge Protection)
Cord Length	1.83 meters
Batteries & Runtime	
Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	16 hour(s)
Replacement Battery	APCRBC106
RBC&#153; Quantity	1
Communications & Management	
Control panel	LED Status display with On Line : On Battery
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Surge Protection and Filtering	
Surge energy rating	310 Joules
Filtering	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449
Data Line Protection	Analog phone line for phone/fax/modem/DSL (RJ-11 connector), Network line - 10/100 Base-T Ethernet (RJ-45 connector)
Physical	
Maximum Height	86.00
Maximum Width	230.00
Maximum Depth	285.00
Net Weight	5.40 KG
Shipping Weight	5.60 KG
Shipping Height	132.00
Shipping Width	300.00
Shipping Depth	366.00
Master Carton Units	2.00
Master Carton Dimensions (Length x Width x Height)	380
Master Carton Weight	12.20 KG
Color	Charcoal
SCC Codes	1073130423340 1
Units per Pallet	48.00
Environmental	
Operating Environment	0 - 40
Operating Relative Humidity	0 - 95
Operating Elevation	0-15000 meters
Storage Temperature	0 - 40
Storage Relative Humidity	0 - 95
Storage Elevation	0-15000 meters
Audible noise at 1 meter from surface of unit	45.00 dBA
Conformance	
Regulatory Approvals	BSI 1363, CE
Standard Warranty	2 years repair or replace, 3 years repair or replace for European Union countries
Equipment protection policy	Lifetime : 50000 GBP

BE400-UK

Sustainable Offer Status	
REACH	REACH: Contains No SVHCs
PEP	Available in Documentation tab
EOL	Available in Documentation tab
Battery Directive	Compliant
Other Environmental Compliance	China RoHS