

1U 17" High Resolution Dual Rail Rackmount LCD Console Drawer

StarTech ID: RACKCOND1701



The RACKCOND1701 1U 17" High Resolution Dual Rail Rackmount LCD Console Drawer offers an LCD display, full keyboard and touchpad console allowing you to centrally manage and monitor your servers and KVM switches using a space-saving 1U of rack space.

An innovative dual-rail system allows the display to slide independently from the keyboard/touchpad tray, giving system administrators the ability to use the device as a monitoring station while the keyboard is neatly tucked away inside the rack. The console supports VGA resolutions up to 1920x1080 for crystal clear display, plus connection to USB or PS/2 based systems/KVM switches for connection flexibility.

With an integrated single port KVM module, the Rack Console is able to connect directly to a single system or to KVM switches in a cascade configuration for centralized control of multiple systems.

Backed by a StarTech.com 3-year warranty and free lifetime technical support.

Applications and Solutions

- Perfect for racks with acrylic or glass doors where you can close the rack but leave the display showing for easy monitoring
- Centralized control of dozens of PCs and servers if used with optional KVM
- Improving the internal space efficiency of existing cabinets
- Manage cabinet mounted servers and KVM switches

Features

- Dual-Rail console design allows display and keyboard/mouse to slide independently
- Supports resolutions up to 1920x1080
- Durable 1U rack mountable design
- Security features, including port locking and auto scan
- On Screen Display (OSD) control and LED indicators for easy monitoring
- Embedded USB-A connectors support wireless keyboard / mouse
- Integrated 106 key US standard keyboard with touchpad

Technical Specifications

- Warranty: 3 Year warranty
- Color: Black
- Connector Types: 2 - DIN 6 Female
- Connector Types: 1 - DB15 Female
- Product Height: 1.72 in [43.8 mm]
- Product Length: 18.93 in [480.8 mm]
- OSD & Hotkey Support: Both hotkeys and OSD (On Screen Display)
- Power Adapter Included: Yes
- Power Adapter - Amperage: 4
- Power Adapter - DC Voltage: 12
- Center Tip Polarity: Positive
- Power Consumption: 16W
- Carton Quantity: 1
- U Height: 1
- Shipping (Package) Weight: 50.61 lb [22.9 kg]
- Product Weight: 550.68 oz [15600 g]
- Product Width: 26.77 in [680 mm]
- Sync: 45~80KHZ
- Chassis Type: Heavy Duty Steel
- Supported Platforms: PS/2, USB, and SUN
- Number of KVM Ports: 1
- Maximum Number of Users: 1

- Maximum Analog Resolutions: 1920x1080
- Display Size: 17.3"
- Panel Type: Active Matrix TFT LCD
- Contrast Ratio: 500:1
- Pixel Pitch Support: 0.199 x 0.199mm
- Viewing Angle: Horizontal -70~70°

Vertical -60~60°

- Console Interface(s): 1 - High Density DB15 (VGA) Male
- Console Interface(s): 2 - 6 pin mini-DIN PS/2 Female
- Console Interface(s): 1 - USB B Female
- Maximum Mounting Depth:: 45.28 in [1150 mm]
- Minimum Mounting Depth:: 23.62 in [600 mm]
- Input Voltage: 110 ~ 240 AC
- Input Current: 1.8 A
- Output Voltage: 12 DC
- Output Current: 4 A
- Humidity: 0~80% RH
- Operating Temperature: 0°C to 40°C (32°F to 104°F)
- Storage Temperature: -20°C to 60°C (-4°F to 140°F)

